

# T3x Treadmill



- LED console display is easily navigated by users of all experience levels
- Low 19 cm / 7.5" step-on height for easy accessibility
- Ultimate Deck System for superior performance and durability
- 4.2hp AC Dynamic Response Drive System

## CONSOLE

Display Type	Dot-matrix LED with profile display
Display Feedback	Speed, Incline, Heart Rate, Time Elapsed, Time Remaining, Time of Day, Total Program Time, Pace, Average Pace, Distance (Miles), Distance (Kilometers), Calories, Calories per Hour, Watts, METs, Workout Profile
User-defined Multi-language Display	No - Accessible through manager menu: English, German, French, Italian, Spanish, Dutch, Portuguese, Japanese, Swedish, Finnish
Workouts	Manual, Rolling Hills, Fat Burn, 5k, Target HR, Gerkin Protocol, Army PFT, Navy PRT, Marine PFT, Air Force PRT, Physical Efficiency Battery (PEB), WFI Protocol
CSAFE Ready-FitLinxx™ Certified	Yes
Netpulse Compatible	Yes
IPTV Compatible	No
FitTouch™ Technology	No
One-button Start	Yes
On-the-fly Program Change	Yes
Integrated Vista Clear™ Television Technology	No
FITCONNEXION™ Ready	Yes
WiFi	No
iPod® Compatible	No
Multimedia Playback	No
Nike + iPod® Compatible	No
Personal Fan	No
USB Port	Yes
Virtual Active™ Compatible	No
Asset Management Compatible	No
mPower Workout Tracking and Fitness Network Compatible	No
Web Connectivity	No
Facility Communication Portal/Calendar	No
Pause Function	Yes
Reading Rack	Yes

## DRIVE SYSTEM

Drive System	Matrix 4.2 hp AC Dynamic Response Drive System <sup>a</sup>
--------------	---

## FEATURES

Deck Type	Ultimate hard-wax reversible 1" deck
Belt Type	Habasit, 2-ply commercial grade
Running Area	152 x 51 cm / 60" x 20"
Step-on Height	19 cm / 7.5"
Cushion System	Ultimate Deck™ cushioning system
Incline Range	0-15% (590-kg / 1,300-lb. thrust elevation motor)
Speed Range	0.8 - 20 km/h / 0.5 - 12 mph
Contact & Telemetric HR	Yes
Crossbar Controls	No
Ethernet Port	Yes

## FRAME

Available Colors	Iced Silver or Matte Black
------------------	----------------------------

## TECH SPECS

Power Requirements	20-amp dedicated circuit required, non-looped grounded
Electrical Receptacle & Plug	NEMA 5-20R 120v
Assembled Dimensions	215 x 85 x 142 cm / 84.6" x 33.5" x 56"
Max User Weight	182 kg / 400 lbs.
Assembled Weight	172 kg / 378 lbs.
Shipping Weight	185 kg / 408 lbs.